AN ORDINANCE TO REPEAL CHAPTER 66, SECTIONS 66-391 THRU 66-425, FLOOD PLAIN DISTRICT, AND ADOPT CHAPTER 28 – FLOODPLAIN, SECTIONS 28.1 THRU 28.61 OF THE CODE OF THE TOWN OF MOUNT JACKSON FOR THE PURPOSE OF UPDATING THE TOWN'S FLOODPLAIN ORDINANCE TO COMPLY WITH FEDERAL AND STATE REGULATIONS

WHEREAS, the Town Council has determined to review and update the Town's floodplain ordinance to ensure compliance with federal and state regulations, and

WHEREAS, the ordinance is proposed to be amended to comply with the most current federal regulations pertaining to the flood insurance program and related statutes promulgated in the Code of Virginia, and to provide references to the federal statute and state code where appropriate.

NOW, THEREFORE, BE IT ORDAINED BY THE Mayor and Town Council of the Town of Mount Jackson that the Chapter 66 Zoning, Sections 66-391 thru 66-425 are hereby repealed and Chapter 28, Sections 28.1 thru 28.61 as depicted in "Attachment A – Ordinance O-07-20" is adopted.

This ordinance shall take effect July 14, 2020.

INTRODUCED at a meeting of the Mayor and Town Council on June 9, 2020.

PASSED by the Council of the Town of Mount Jackson, Virginia, on the 14th day of July, 2020.

Deborah A. Stover, Town Clerk	Donald I. Pifer, Mayor

CHAPTER 28

FLOODPLAIN

Contents

Article I. GENERAL PROVISIONS	2
Section 28.1 Statutory authorization and purpose [44 CFR 59.22(a)(2)]	2
Section 28.2. – Applicability.	2
Section 28.3 - Compliance and liability	2
Section 28.4 Records [44 CFR 59.22(a)(9)(iii)]	3
Section 28.5 Abrogation and greater restrictions [44 CFR 60.1(b)].	3
Section 28.6. – Severability.	
Section 28.7 - Penalty for violations [44 CFR 60.2(e)].	3
ARTICLE II - ADMINISTRATION	4
Section 28.20 Designation of the floodplain administrator [44 CFR 59.22(b)]	4
Section 28.21 Duties and responsibilities of the floodplain administrator [44 CFR 60.3	
Section 28.22 Use and interpretation of FIRMs [44 CFR 60.3]	6
Section 28.23 - Jurisdictional boundary changes [44 CFR 59.22, 65.3].	7
Section 28.24 District boundary changes.	7
Section 28.25 - Interpretation of district boundaries.	7
Section 28.26 Submitting model backed technical data [44 CFR 65.3]	8
Section 28.27 Letters of map revision (LOMR).	8
ARTICLE III - ESTABLISHMENT OF FLOOD HAZARD DISTRICTS	9
Section 28.30 Description of Special Flood Hazard Districts [44 CFR 59.1, 60.3]	9
ARTICLE IV - DISTRICT PROVISIONS [44 CFR 59.22, 60.2, 60.3]	12
Section 28.40 Permit and application requirements.	12
Section 28.41 General standards.	12
Section 28.42 Elevation and construction standards [44 CFR 60.3].	13
Section 28.43 Standards for subdivision proposals.	16
ARTICLE V – EXISTING STRUCTURES IN FLOODPLAIN AREAS	17
Section 28.50. – Existing structures.	17
ARTICLE VI - VARIANCES: FACTORS TO BE CONSIDERED [44 CFR 60.6]	18
Section 28.50 Factors to be considered.	18
Article VII - DEFINTIONS [44 CFR 59.1].	20

Article I. GENERAL PROVISIONS

Section 28.1. - Statutory authorization and purpose [44 CFR 59.22(a)(2)].

Virginia Code § 15.2-2283, as amended, specifies that zoning ordinances shall be for the general purpose of promoting the health, safety, or general welfare of the public and of further accomplishing the objectives of Virginia Code §15.2-2200, as amended which encourages localities to improve the public health, safety, convenience, and welfare of their citizens. To these ends, flood ordinances shall be designed to provide for safety from flood, to facilitate the provision of flood protection, and to protect against loss of life, health, or property from flood.

In accordance with these directed provisions, this ordinance is specifically adopted pursuant to the authority granted to localities by Virginia Code \$15.2 - 2280, as amended.

The purpose of these provisions is to prevent: the loss of life, health, or property, the creation of health and safety hazards, the disruption of commerce and governmental services, the extraordinary and unnecessary expenditure of public funds for flood protection and relief, and the impairment of the tax base by:

- 1) Regulating uses, activities, and development which, alone or in combination with other existing or future uses, activities, and development, will cause unacceptable increases in flood heights, velocities, and frequencies;
- 2) Restricting or prohibiting certain uses, activities, and development from locating within districts subject to flooding;
- Requiring all those uses, activities, and developments that do occur in flood-prone districts to be protected and/or floodproofed against flooding and flood damage; and
- 4) Protecting individuals from buying land and structures which are unsuited for intended purposes because of flood hazards.

Section 28.2. – Applicability.

These provisions shall apply to all privately and publicly owned lands within the jurisdiction of Town of Mount Jackson and identified as a special flood hazard area (SFHA) identified by the town or shown on the flood insurance rate map (FIRM) or included in the flood insurance study (FIS) that are provided to the town by the Federal Emergency Management Association (FEMA).

Section 28.3 - Compliance and liability.

- a) No land shall hereafter be developed and no structure shall be located, relocated, constructed, reconstructed, enlarged, or structurally altered except in full compliance with the terms and provisions of this ordinance and any other applicable ordinances and regulations which apply to uses within the jurisdiction of this ordinance.
- b) The degree of flood protection sought by the provisions of this ordinance is considered reasonable for regulatory purposes and is based on acceptable engineering methods of study but does not imply total flood protection. Larger floods may occur on rare occasions. Flood heights may be increased by man-made or natural causes, such as ice

jams and bridge openings restricted by debris. This ordinance does not imply that districts outside the floodplain district or land uses permitted within such district will be free from flooding or flood damages.

c) This ordinance shall not create liability on the part of the town or any officer or employee thereof for any flood damages that result from reliance on this ordinance or any administrative decision lawfully made thereunder.

Section 28.4. - Records [44 CFR 59.22(a)(9)(iii)].

Records of actions associated with administering this ordinance shall be kept on file and maintained by or under the direction of the floodplain administrator in perpetuity.

Section 28.5. - Abrogation and greater restrictions [44 CFR 60.1(b)].

To the extent that the provisions are more restrictive, this ordinance supersedes any ordinance currently in effect in flood-prone districts. To the extent that any other existing law or regulation is more restrictive or does not conflict it shall remain in full force and effect.

These regulations are not intended to repeal or abrogate any existing ordinances including subdivision regulations, zoning ordinances, or building codes. In the event of a conflict between these regulations and any other ordinance, the more restrictive shall govern.

Section 28.6. – Severability.

If any section, subsection, paragraph, sentence, clause, or phrase of this ordinance shall be declared invalid for any reason whatever, such decision shall not affect the remaining portions of this ordinance. The remaining portions shall remain in full force and effect; and for this purpose, the provisions of this ordinance are hereby declared to be severable.

Section 28.7 - Penalty for violations [44 CFR 60.2(e)].

Any person who fails to comply with any of the requirements or provisions of this article or directions of the floodplain administrator or any authorized employee of the town shall be guilty of a class 1 misdemeanor as defined in §1-8(b) of the town code and subject to the penalties thereof. The VA USBC addresses building code violations and the associated penalties in §§ 104 and 115.

In addition to the above penalties, all other actions are hereby reserved, including an action in equity for the proper enforcement of this article. The imposition of a fine or penalty for any violation of, or noncompliance with, this article shall not excuse the violation or noncompliance or permit it to continue; and all such persons shall be required to correct or remedy such violations within a reasonable time. Any structure constructed, reconstructed, enlarged, altered or relocated in noncompliance with this article may be declared by the town council to be a public nuisance and abatable as such. Flood insurance may be withheld from structures constructed in violation of this article.

ARTICLE II - ADMINISTRATION

Section 28.20. - Designation of the floodplain administrator [44 CFR 59.22(b)].

The floodplain administrator is hereby appointed by council to administer and implement these regulations. The floodplain administrator may:

- 1) Perform the duties and responsibilities as set forth in these regulations;
- 2) Delegate duties and responsibilities set forth in these regulations to qualified technical personnel, plan examiners, inspectors, and other employees; and/or
- 3) Enter into a written agreement or written contract with another community or private sector entity to administer specific provisions of these regulations. Administration of any part of these regulations by another entity shall not relieve the community of its responsibilities pursuant to the participation requirements of the National Flood Insurance Program as set forth in the Code of Federal Regulations at 44 C.F.R. 59.22.

Section 28.21. - Duties and responsibilities of the floodplain administrator [44 CFR 60.3].

The duties and responsibilities of the floodplain administrator shall include but are not limited to:

- 1) Review an application for permit to determine whether proposed activities will be located in a SFHA.
- 2) Interpret floodplain boundaries and provide available base flood elevation and flood hazard information.
- 3) Review applications to determine whether proposed activities will be reasonably safe from flooding and require new construction and substantial improvements to meet the requirements of these regulations.
- 4) Review applications to determine whether all necessary permits have been obtained from the federal, state, or local agencies from which prior or concurrent approval is required; in particular, permits from state agencies for any construction, reconstruction, repair, or alteration of a dam, reservoir, or waterway obstruction (including bridges, culverts, structures), any alteration of a watercourse, or any change of the course, current, or cross section of a stream or body of water, including any change to the 100-year frequency floodplain of free-flowing non-tidal waters of the State.
- 5) Verify that an applicant proposing to alter a watercourse has notified adjacent local governments, the Department of Conservation and Recreation, Division of Dam Safety and Floodplain Management (DCR), the Virginia Department of Environmental Quality (DEQ), and the US Army Corp of Engineers (USACE), and has submitted copies of such notifications to FEMA.
- 6) Approve applications and issue permits to develop in SFHA if the provisions of these regulations have been met or disapprove applications if the provisions of these regulations have not been met.
- 7) Inspect or cause to be inspected, buildings, structures, and other development for which permits have been issued to determine compliance with these regulations or to determine if non-compliance has occurred or violations have been committed.
- 8) Review elevation certificates and require incomplete or deficient certificates to be corrected.

- 9) Submit to FEMA, or require applicants to submit to FEMA, data and information necessary to maintain the FIRM, including hydrologic and hydraulic engineering analyses prepared by or for the town, within six months after such data and information becomes available, if the analyses indicate changes in base flood elevations.
- 10) Maintain and permanently keep records that are necessary for the administration of these regulations, including:
 - a. Copies of FIS, FIRM (including historic studies and maps and current effective studies and maps), and Letters of Map Change (LOMC); and
 - b. Documentation supporting issuance and denial of permits, elevation certificates, documentation of the elevation (in relation to the datum on the FIRM) to which structures have been floodproofed, inspection records, other required design certifications, variances, and records of enforcement actions taken to correct violations of these regulations.
- 11) Enforce the provisions of these regulations, investigate violations, issue notices of violations or stop work orders, and require permit holders to take corrective action.
- 12) Advise the board of zoning appeals regarding the intent of these regulations and prepare a staff report and recommendation for each application for a variance.
- 13) Administer the requirements related to proposed work on existing buildings:
 - a. Determine if buildings and structures located in SFHA have been substantially damaged.
 - b. Make a reasonable effort to notify the owner(s) of substantially damaged structures of the need to obtain a permit to repair, rehabilitate, or reconstruct the structure. Prohibit the repair of a substantially damaged building without a permit, except for temporary emergency protective measures necessary to secure a property or to stabilize a building or structure to prevent additional damage.
- 14) Undertake, as deemed appropriate, other actions, which may include but are not limited to: issuing a press release, a public service announcement, or provide other public information materials related to permit requests and repair of damaged structures; coordinate with other federal, state and local agencies to assist with substantial damage determinations; provide owners of damaged structures information related to the proper repair of damaged structures in special flood hazard areas; and assist property owners with documentation necessary to file claims for Increased Cost of Compliance (ICC) coverage under NFIP flood insurance policies.
- 15) Notify FEMA when the corporate boundaries of the town have been modified and:
 - a. Provide a map that clearly delineates the new corporate boundaries or the new area for which the authority to regulate pursuant to these regulations has either been assumed or relinquished through annexation; and
 - b. If the FIRM for any annexed area includes special flood hazard areas that have flood zones that have regulatory requirements that are not set forth in these regulations, prepare amendments to these regulations to adopt the FIRM and appropriate requirements, and submit the amendments to the governing body for adoption; such adoption shall take place at the same time as or prior to the date of annexation and a copy of the amended regulations shall be provided to DCR and FEMA.

- 16) Upon the request of FEMA, complete and submit a report concerning participation in the NFIP which may request information regarding the number of buildings in the SFHA, number of permits issued for development in the SFHA, and number of variances issued for development in the SFHA.
- 17) It is the duty of the floodplain administrator to take into account flood, mudslide and flood-related erosion hazards, to the extent that they are known, in all official actions relating to land management and use throughout the town, whether or not those hazards have been specifically delineated geographically (e.g. via mapping or surveying).

Section 28.22. - Use and interpretation of FIRMs [44 CFR 60.3].

The floodplain administrator shall make interpretations, where needed, as to the exact location of special flood hazard areas, floodplain boundaries, and floodway boundaries. The following shall apply to the use and interpretation of FIRMs and data:

- 1) Where field surveyed topography indicates that adjacent ground elevations:
 - a. Are below the base flood elevation in riverine SFHAs, or below the 1% storm surge elevation in coastal SFHAs, even in areas not delineated as a special flood hazard area on a FIRM, the area shall be considered as area SFHA and subject to the requirements of these regulations;
 - b. Are above the base flood elevation and the area is labelled as a SFHA on the FIRM, the area shall be regulated as area SFHA unless the applicant obtains a LOMC that removes the area from the SFHA.
- 2) In FEMA-identified SFHAs where base flood elevation and floodway data have not been identified, and in areas where FEMA has not identified SFHAs, other flood hazard data available from federal or state agencies or other certified source shall be reviewed and reasonably used.
- 3) Base flood elevations and designated floodway boundaries on FIRMs and in FISs shall take precedence over base flood elevations and floodway boundaries provided by any other sources, if such sources show reduced floodway widths and/or lower base flood elevations.
- 4) Other sources of data shall be reasonably used if such sources show increased base flood elevations and/or larger floodway areas than are shown on FIRMs and in FISs.
- 5) If a preliminary FIRM and/or a preliminary FIS has been provided by FEMA:
 - a. Upon the issuance of a Letter of Final Determination (LOFD) by FEMA, the preliminary flood hazard data shall be used and shall replace the flood hazard data previously provided from FEMA for the purposes of administering these regulations.
 - b. Prior to the issuance of a LOFD by FEMA, the use of preliminary flood hazard data shall be deemed the best available data pursuant to \$28.30.3 and used where no base flood elevations and/or floodway areas are provided on the effective FIRM.
 - c. Prior to issuance of a LOFD by FEMA, the use of preliminary flood hazard data is permitted where the preliminary base flood elevations or floodway areas exceed the base flood elevations and/or designated floodway widths in existing flood hazard data provided by FEMA. Such preliminary data may be subject to change and/or appeal to FEMA.

Section 28.23 - Jurisdictional boundary changes [44 CFR 59.22, 65.3].

The county floodplain ordinance in effect on the date of annexation shall remain in effect and shall be enforced by the town for all annexed areas until council adopts and enforces an ordinance meeting the requirements for participation in the NFIP. The town shall pass a resolution acknowledging and accepting responsibility for enforcing floodplain ordinance standards prior to annexation of any area containing identified flood hazards. If the FIRM for any annexed area includes special flood hazard areas that have flood zones that have regulatory requirements that are not set forth in these regulations, the town manager shall prepare amendments to these regulations to adopt the FIRM and appropriate requirements, and submit the amendments to council for adoption; such adoption shall take place at the same time as or prior to the date of annexation and a copy of the amended regulations shall be provided to DCR and FEMA.

In accordance with the Code of Federal Regulations, Title 44 Subpart (B) §59.22(a)(9)(v) the town will notify the Federal Insurance Administration (FIA) and the state coordinating office in writing whenever the boundaries of the town have been modified by annexation or the community has otherwise assumed or no longer has authority to adopt and enforce floodplain management regulations for a particular area.

In order that the FIRM accurately represent the town's boundaries, a copy of a map of the town suitable for reproduction, clearly delineating the new corporate limits or new area for which the community has assumed or relinquished floodplain management regulatory authority must be included with the notification.

Section 28.24. - District boundary changes.

The delineation of floodplain districts may be revised by the town where natural or manmade changes have occurred and/or where more detailed studies have been conducted or undertaken by the USACE or other qualified agency, or an individual provides the information necessary for such change. However, prior to any such change, approval must be obtained from FEMA. A completed LOMR is a record of this approval.

Section 28.25 - Interpretation of district boundaries.

Initial interpretations of the boundary of a floodplain district shall be made by the zoning administrator. Should a dispute arise concerning the boundary of any district, the board of zoning appeals shall make the necessary determination. The person questioning or contesting the location of the district boundary shall be given a reasonable opportunity to provide information and technical evidence to the board.

Section 28.26. - Submitting model backed technical data [44 CFR 65.3].

The town's base flood elevations may increase or decrease resulting from physical changes affecting flooding conditions. As soon as practicable, but not later than six months after the date such information becomes available, the town shall notify FEMA of the changes by submitting technical or scientific data. The town may submit data via a LOMR. Such a submission is necessary so that upon confirmation of those physical changes affecting flooding conditions, risk premium rates and floodplain management requirements will be based upon current data.

Section 28.27. - Letters of map revision (LOMR).

When development in the floodplain will cause or causes a change in the base flood elevation, the applicant, including state agencies, must notify FEMA by applying for a Conditional Letter of Map Revision (CLOMR) and then a LOMR.

Examples include:

- 1) Any development that causes a rise in the base flood elevations within the floodway.
- 2) Any development occurring in Zones A1-30 and AE without a designated floodway, which will cause a rise of more than one foot in the base flood elevation.
- 3) Alteration or relocation of a stream (including but not limited to installing culverts and bridges) *Code of Federal Regulations Title 44 §§65.3 and 65.6(a)(12)*.

Section 28.28 – 28.99. Reserved

ARTICLE III - ESTABLISHMENT OF FLOOD HAZARD DISTRICTS

Section 28.30. - Description of Special Flood Hazard Districts [44 CFR 59.1, 60.3].

Basis of districts. The various special flood hazard districts shall include the SFHAs. The basis for the delineation of these districts shall be the FIS and the FIRM for the town prepared by FEMA, FIA, dated 07/16/03, and any subsequent revisions or amendments thereto.

The town may identify and regulate local flood hazard or ponding areas that are not delineated on the FIRM. These areas may be delineated on a Local Flood Hazard Map (LFHM) using best available topographic data and locally derived information such as flood of record, historic high-water marks, or approximate study methodologies.

The boundaries of the SFHA Districts are established as shown on the FIRM which is declared to be a part of this ordinance and which shall be kept on file at the town offices.

1) The floodway district is in an AE Zone and is delineated, for purposes of this ordinance, using the criterion that certain areas within the floodplain must be capable of carrying the waters of the one percent annual chance flood without increasing the water surface elevation of that flood more than one (1) foot at any point.

The following provisions shall apply within the floodway district of an AE zone [44 CFR 60.3(d)]:

a. Within any floodway area, no encroachments, including fill, new construction, substantial improvements, or other development shall be permitted unless it has been demonstrated through hydrologic and hydraulic analysis performed in accordance with standard engineering practice that the proposed encroachment will not result in any increase in flood levels within the community during the occurrence of the base flood discharge. Hydrologic and hydraulic analyses shall be undertaken only by professional engineers or others of demonstrated qualifications, who shall certify that the technical methods used correctly reflect currently accepted technical concepts. Studies, analyses, computations, etc., shall be submitted in sufficient detail to allow a thorough review by the floodplain administrator.

Development activities which increase the water surface elevation of the base flood may be allowed, provided that the applicant first applies – with the town's endorsement – for a Conditional Letter of Map Revision (CLOMR), and receives the approval of FEMA.

If §28-30 is satisfied, all new construction and substantial improvements shall comply with all applicable flood hazard reduction provisions of article IV.

- b. The placement of manufactured homes (mobile homes) is prohibited, except in an existing manufactured home (mobile home) park or subdivision. A replacement manufactured home may be placed on a lot in an existing manufactured home park or subdivision provided the anchoring, elevation, and encroachment standards are met.
- 2) The AE zone on the FIRM accompanying the FIS shall be those areas for which one-percent annual chance flood elevations have been provided and the floodway has not been delineated. The following provisions shall apply within an AE zone [44 CFR 60.3(c)] where FEMA has provided base flood elevations:

Until a regulatory floodway is designated, no new construction, substantial improvements, or other development (including fill) shall be permitted within the areas of special flood hazard, designated as a AE zone on the FIRM, unless it is demonstrated that the cumulative effect of the proposed development, when combined with all other existing and anticipated development, will not increase the water surface elevation of the base flood more than one foot at any point within the town.

Development activities in AE zone on the town's FIRM which increase the water surface elevation of the base flood by more than one foot may be allowed, provided that the applicant first applies – with the town's endorsement – for a CLMR, and receives the approval of FEMA.

3) The A Zone on the FIRM accompanying the FIS shall be those areas for which no detailed flood profiles or elevations are provided, but the one percent annual chance floodplain boundary has been approximated. For these areas, the following provisions shall apply [44 CFR 60.3(b)]:

The approximated floodplain district (AFD) shall be that floodplain area for which no detailed flood profiles or elevations are provided, but where a one percent annual chance floodplain boundary has been approximated. Such areas are shown as Zone A on the maps accompanying the FIS. For these areas, the base flood elevations and floodway information from federal, state and other acceptable sources shall be used, if available. Where the specific one percent annual chance flood elevation cannot be determined for this area using other sources of data, such as the USACE floodplain information reports, U. S. Geological Survey (USGS) flood-prone quadrangles, etc., then the applicant for the proposed use, development and/or activity shall determine this base flood elevation. For development proposed in the approximate floodplain the applicant must use technical methods that correctly reflect currently accepted practices, such as point on boundary, high water marks, or detailed methodologies hydrologic and hydraulic analyses. Studies, analyses, computations, etc., shall be submitted in sufficient detail to allow a thorough review by the floodplain administrator.

The floodplain administrator reserves the right to require a hydrologic and hydraulic analysis for any development. When such base flood elevation data is

utilized, the lowest floor shall be elevated to or above the base flood level plus eighteen (18) inches of freeboard.

During the permitting process, the administrator shall obtain:

- a. The elevation of the lowest floor (in relation to mean sea level), including the basement, of all new and substantially improved structures; and,
- b. If the structure has been floodproofed in accordance with the requirements of this article, the elevation (in relation to mean sea level) to which the structure has been floodproofed.

Base flood elevation data shall be obtained from other sources or developed using detailed methodologies comparable to those contained in a FIS for subdivision proposals and other proposed development proposals (including manufactured home parks and subdivisions) that exceed five lots or five acres, whichever is the lesser.

Section 28.31 – 28.39. Reserved.

ARTICLE IV - DISTRICT PROVISIONS [44 CFR 59.22, 60.2, 60.3]

Section 28.40. - Permit and application requirements.

a) Permit requirement.

All uses, activities, and development occurring within any floodplain district, including placement of manufactured homes, shall be undertaken only upon the issuance of a permit. Such development shall be undertaken only in strict compliance with the provisions of this ordinance and with all other applicable codes and ordinances, as amended, such as the Virginia Uniform Statewide Building Code (VA USBC) and chapter 50, subdivision, of this code. Prior to the issuance of any such permit, the floodplain administrator shall require all applications to include compliance with all applicable federal and state laws and shall review all sites to assure they are reasonably safe from flooding. Under no circumstances shall any use, activity, and/or development adversely affect the capacity of the channels or floodway of any watercourse, drainage ditch, or any other drainage facility or system.

b) Site plans and permit applications.

All applications for development within any floodplain district and all permits issued for the floodplain shall incorporate the following information:

- 1) The elevation of the base flood at the site.
- 2) For structures to be elevated, the elevation of the lowest floor (including basement) or, in V zones, the lowest horizontal structural member.
- 3) For structures to be floodproofed (non-residential only), the elevation to which the structure will be floodproofed.
- 4) Topographic information showing existing and proposed ground elevations.

Section 28.41. - General standards.

The following provisions shall apply to all permits:

- 1) New construction and substantial improvements shall be built according to this ordinance and the VA USBC, and anchored to prevent flotation, collapse, or lateral movement of the structure.
- 2) Manufactured homes shall be anchored to prevent flotation, collapse, or lateral movement. Methods of anchoring may include, but are not limited to, use of overthe-top or frame ties to ground anchors. This standard shall be in addition to and consistent with applicable state anchoring requirements for resisting wind forces.
- 3) New construction and substantial improvements shall be constructed with materials and utility equipment resistant to flood damage.
- 4) New construction or substantial improvements shall be constructed by methods and practices that minimize flood damage.

- 5) Electrical, heating, ventilation, plumbing, air conditioning equipment, and other service facilities, including duct work, shall be designed and/or located to prevent water from entering or accumulating within the components during conditions of flooding.
- 6) New and replacement water supply systems shall be designed to minimize or eliminate infiltration of flood waters into the system.
- 7) New and replacement sanitary sewage systems shall be designed to minimize or eliminate infiltration of flood waters into the systems and discharges from the systems into flood waters.
- 8) On-site waste disposal systems shall be located and constructed to avoid impairment to them or contamination from them during flooding.

In addition to provisions 1 - 8 above, in all SFHA, the additional provisions shall apply:

- 9) Prior to any proposed alteration or relocation of any channels or of any watercourse, stream, etc., within the town a permit shall be obtained from the USCE, DEQ, and the Virginia Marine Resources Commission (VMRC). A joint permit application is available from any of these agencies. Furthermore, in riverine areas, notification of the proposal shall be given by the applicant to all affected adjacent localities, DCR, other required agencies, and FEMA.
- 10) The flood carrying capacity within an altered or relocated portion of any watercourse shall be maintained.

Section 28.42. - Elevation and construction standards [44 CFR 60.3].

In all identified flood hazard areas where base flood elevations have been provided in the FIS or generated by a certified professional in accordance with §28-30.3 the following provisions shall apply:

1) Residential construction.

New construction or substantial improvement of any residential structure (including manufactured homes) in Zones AE and A with detailed base flood elevations shall have the lowest floor, including basement, elevated to or above the base flood level plus 18" of freeboard. See §28.30 for requirements in the coastal A, VE, and V zones.

2) Non-Residential Construction

- a. New construction or substantial improvement of any commercial, industrial, or non-residential building (or manufactured home) shall have the lowest floor, including basement, elevated to or above the base flood level plus 18" of freeboard.
- b. Non-residential buildings located in all AE zones may be floodproofed in lieu of being elevated provided that all areas of the building components below the elevation corresponding to the BFE plus 18" are water tight with walls substantially impermeable to the passage of water, and use structural components having the capability of resisting hydrostatic and hydrodynamic loads and the effect of buoyancy. A registered professional engineer or architect shall certify that the standards of this subsection are satisfied. Such certification, including the specific elevation (in relation to mean sea level) to which such structures are floodproofed, shall be maintained by floodplain administrator.
- 3) Space below the lowest floor.
 - In zones A and AE fully enclosed areas, of new construction or substantially improved structures, which are below the regulatory flood protection elevation shall:
 - a. Not be designed or used for human habitation, but shall be used solely for parking of vehicles, building access, or limited storage of maintenance equipment used in connection with the premises. Access to the enclosed area shall be the minimum necessary to allow for parking of vehicles (garage door) or limited storage of maintenance equipment (standard exterior door), or entry to the living area (stairway or elevator).
 - b. Be constructed entirely of flood resistant materials below the regulatory flood protection elevation;
 - c. Include measures to automatically equalize hydrostatic flood forces on walls by allowing for the entry and exit of floodwaters. To meet this requirement, the openings must either be certified by a professional engineer or architect or meet the following minimum design criteria:
 - (i) Provide a minimum of two openings on different sides of each enclosed area subject to flooding.
 - (ii) The total net area of all openings must be at least one square inch for each square foot of enclosed area subject to flooding.
 - (iii)If a building has more than one enclosed area, each area must have openings to allow floodwaters to automatically enter and exit.
 - (iv) The bottom of all required openings shall be no higher than one foot above the adjacent grade.
 - (v) Openings may be equipped with screens, louvers, or other opening coverings or devices, provided they permit the automatic flow of floodwaters in both directions.
 - (vi)Foundation enclosures made of flexible skirting are not considered enclosures for regulatory purposes, and, therefore, do not require openings. Masonry or wood underpinning, regardless of structural status, is considered an enclosure and requires openings as outlined above.

4) Accessory Structures

In addition to meeting all other design and performance standards identified in 44 C.F.R. §60.3 and the Virginia Uniform Statewide Building Code (VA USBC) as applicable to non-residential structures, accessory structures in the SFHA shall comply with the elevation requirements and other requirements of §28-42.2 and,

- a. Not be used for human habitation;
- b. Be limited to no more than 300 square feet in total floor area;
- c. Be useable only for parking of vehicles or limited storage;
- d. Be constructed with flood damage-resistant materials below the base flood elevation;
- e. Be constructed and placed to offer the minimum resistance to the flow of floodwaters;
- f. Be anchored to prevent flotation;
- g. Have electrical service and mechanical equipment elevated to or above the base flood elevation;
- h. Shall be provided with flood openings which shall meet the following criteria:
 - (i) There shall be a minimum of two flood openings on different sides of each enclosed area; if a building has more than one enclosure below the lowest floor, each such enclosure shall have flood openings on exterior walls.
 - (ii) The total net area of all flood openings shall be at least 1 square inch for each square foot of enclosed area (non-engineered flood openings), or the flood openings shall be engineered flood openings that are designed and certified by a licensed professional engineer to automatically allow entry and exit of floodwaters; the certification requirement may be satisfied by an individual certification or an evaluation report issued by the ICC Evaluation Service, Inc.
 - (iii) The bottom of each flood opening shall be 1 foot or less above the higher of the interior floor or grade, or the exterior grade, immediately below the opening.
 - (iv) Any louvers, screens or other covers for the flood openings shall allow the automatic flow of floodwaters into and out of the enclosed area.
- i. A signed non-conversion agreement shall be recorded on the property deed prior to final inspection..

5) Standards for Manufactured Homes and Recreational Vehicles

- a. In zones A and AE, all manufactured homes placed, or substantially improved, on individual lots or parcels, must meet all the requirements for new construction, including the elevation and anchoring requirements in §\$28.41 and 28.42.
- b. All recreational vehicles placed on sites must either:
 - (i) Be on the site for fewer than 180 consecutive days, be fully licensed and ready for highway use (a recreational vehicle is ready for highway use if it is on its wheels or jacking system, is attached to the site only by quick disconnect type utilities and security devices and has no permanently attached additions); or
 - (ii) Meet all the requirements for manufactured homes in subparagraph a above.

Section 28.43. - Standards for subdivision proposals.

- a) All subdivision proposals shall be consistent with the need to minimize flood damage;
- b) All subdivision proposals shall have public utilities and facilities such as sewer, gas, electrical and water systems located and constructed to minimize flood damage;
- c) All subdivision proposals shall have adequate drainage provided to reduce exposure to flood hazards, and
- d) Base flood elevation data shall be obtained from other sources or developed using detailed methodologies, hydraulic and hydrologic analysis, comparable to those contained in a FIS for subdivision proposals and other proposed development proposals (including manufactured home parks and subdivisions) that exceed five lots or five acres, whichever is the lesser.

Section 28.44 – 28.49. Reserved.

ARTICLE V – EXISTING STRUCTURES IN FLOODPLAIN AREAS

Section 28.50. – Existing structures.

Any structure or use of a structure or premises must be brought into conformity with these provisions when it is changed, repaired, or improved unless one of the following exceptions is established before the change is made:

- 1) The floodplain manager determines that:
 - a. Change is not a substantial repair or substantial improvement;
 - b. No new square footage is being built in the floodplain that is not complaint;
 - c. No new square footage is being built in the floodway; and
 - d. The change complies with this ordinance and the VA USBC.
- 2) The changes are required to comply with a citation for a health or safety violation.
- 3) The structure is a historic structure and the change required would impair the historic nature of the structure.

Section 28.51 – 28.59. Reserved.

ARTICLE VI - VARIANCES: FACTORS TO BE CONSIDERED [44 CFR 60.6]

Section 28.50. - Factors to be considered.

- a) Variances shall be issued only upon:
 - 1) a showing of good and sufficient cause,
 - 2) after the board of zoning appeals (BZA) has determined that failure to grant the variance would result in exceptional hardship to the applicant, and
 - 3) after the BZA has determined that the granting of such variance will not result in:
 - a. unacceptable or prohibited increases in flood heights,
 - b. additional threats to public safety,
 - c. extraordinary public expense; and
 - d. will not create nuisances, cause fraud or victimization of the public, or conflict with local laws or ordinances.
- b) While the granting of variances generally is limited to a lot size less than one-half acre, deviations from that limitation may occur. However, as the lot size increases beyond one-half acre, the technical justification required for issuing a variance increases. Variances may be issued by the BZA for new construction and substantial improvements to be erected on a lot of one-half acre or less in size contiguous to and surrounded by lots with existing structures constructed below the base flood level, in conformance with the provisions of this section.
- c) Variances may be issued for new construction and substantial improvements and for other development necessary for the conduct of a functionally dependent use provided that the criteria of this section are met, and the structure or other development is protected by methods that minimize flood damages during the base flood and create no additional threats to public safety.
- d) In passing upon applications for variances, the BZA shall satisfy all relevant factors and procedures specified in the zoning ordinance and consider the following additional factors:
 - 1) The danger to life and property due to increased flood heights or velocities caused by encroachments. No variance shall be granted for any proposed use, development, or activity within any floodway district that will cause any increase in the one percent (1%) chance flood elevation.
 - 2) The danger that materials may be swept on to other lands or downstream to the injury of others.
 - 3) The proposed water supply and sanitation systems and the ability of these systems to prevent disease, contamination, and unsanitary conditions.
 - 4) The susceptibility of the proposed facility and its contents to flood damage and the effect of such damage on the individual owners.
 - 5) The importance of the services provided by the proposed facility to the community.
 - 6) The requirements of the facility for a waterfront location.
 - 7) The availability of alternative locations not subject to flooding for the proposed use.

- 8) The compatibility of the proposed use with existing development and development anticipated in the foreseeable future.
- 9) The relationship of the proposed use to the comprehensive plan and floodplain management program for the area.
- 10) The safety of access by ordinary and emergency vehicles to the property in time of flood.
- 11) The expected heights, velocity, duration, rate of rise, and sediment transport of the flood waters expected at the site.
- 12) The historic nature of a structure. Variances for repair or rehabilitation of historic structures may be granted upon a determination that the proposed repair or rehabilitation will not preclude the structure's continued designation as a historic structure and the variance is the minimum necessary to preserve the historic character and design of the structure.
- 13) No variance shall be granted for an accessory structure exceeding 300 square feet. See §28.42.4.b.
- 14) Such other factors which are relevant to the purposes of this ordinance.
- e) The BZA may refer any application and accompanying documentation pertaining to any request for a variance to any engineer or other qualified person or agency for technical assistance in evaluating the proposed project in relation to flood heights and velocities, and the adequacy of the plans for flood protection and other related matters.
- f) Variances shall be issued only after the BZA has determined that the granting of such will not result in (a) unacceptable or prohibited increases in flood heights, (b) additional threats to public safety, (c) extraordinary public expense; and will not (d) create nuisances, (e) cause fraud or victimization of the public, or (f) conflict with local laws or ordinances.
- g) Variances shall be issued only after the BZA has determined that the variance will be the minimum required to provide relief.
- h) The BZA shall notify the applicant for a variance, in writing that the issuance of a variance to construct a structure below the one percent (1%) chance flood elevation (a) increases the risks to life and property and (b) will result in increased premium rates for flood insurance.
- A record shall be maintained of the above notification as well as all variance actions, including justification for the issuance of the variances. Any variances that are issued shall be noted in the annual or biennial report submitted to the federal insurance administrator.

Sections 28.61 – 28. 69. Reserved.

Article VII - DEFINTIONS [44 CFR 59.1].

Appurtenant or accessory structure - A non-residential structure which is on the same parcel of property as the principal structure and the use of which is incidental to the use of the principal structure. Accessory structures are not to exceed 300 square feet.

Base flood - The flood having a one percent chance of being equalled or exceeded in any given year.

Base flood elevation - The water surface elevations of the base flood, that is, the flood level that has a one percent or greater chance of occurrence in any given year. The water surface elevation of the base flood in relation to the datum specified on the community's Flood Insurance Rate Map. For the purposes of this ordinance, the base flood is the 1% annual chance flood.

Basement - Any area of the building having its floor sub-grade (below ground level) on all sides.

Board of Zoning Appeals - The board appointed to review appeals made by individuals with regard to decisions of the zoning administrator in the interpretation of this ordinance. Also referred to as BZA.

Coastal A Zone - Flood hazard areas that have been delineated as subject to wave heights between 1.5 feet and 3 feet.

Development - Any man-made change to improved or unimproved real estate, including, but not limited to, buildings or other structures, temporary structures, mining, dredging, filling, grading, paving, excavation, drilling or other land-disturbing activities or permanent or temporary storage of equipment or materials.

Elevated building - A non-basement building built to have the lowest floor elevated above the ground level by means of solid foundation perimeter walls, pilings, or columns (posts and piers).

Encroachment - The advance or infringement of uses, plant growth, fill, excavation, buildings, permanent structures or development into a floodplain, which may impede or alter the flow capacity of a floodplain.

Existing construction - For the purposes of the insurance program, structures for which the "start of construction" commenced before the effective date of the FIRM or before January 1, 1975 for FIRMs effective before that date. "Existing construction" may also be referred to as "existing structures" and "pre-FIRM."

Flood or flooding - means

- 1) A general or temporary condition of partial or complete inundation of normally dry land areas from:
 - a. The overflow of inland or tidal waters; or,
 - b. The unusual and rapid accumulation or runoff of surface waters from any source.

- c. Mudflows which are proximately caused by flooding as defined in paragraph (1)(b) of this definition and are akin to a river of liquid and flowing mud on the surfaces of normally dry land areas, as when earth is carried by a current of water and deposited along the path of the current.
- 2) The collapse or subsidence of land along the shore of a lake or other body of water as a result of erosion or undermining caused by waves or currents of water exceeding anticipated cyclical levels or suddenly caused by an unusually high water level in a natural body of water, accompanied by a severe storm, or by an unanticipated force of nature such as flash flood or an abnormal tidal surge, or by some similarly unusual and unforeseeable event which results in flooding as defined in paragraph 1 (a) of this definition.

Flood Insurance Rate Map (FIRM) - an official map of a community, on which FEMA has delineated both the special hazard areas and the risk premium zones applicable to the community. A FIRM that has been made available digitally is called a Digital Flood Insurance Rate Map (DFIRM).

Flood Insurance Study (FIS) - a report by FEMA that examines, evaluates and determines flood hazards and, if appropriate, corresponding water surface elevations, or an examination, evaluation and determination of mudflow and/or flood-related erosion hazards.

Floodplain or flood-prone area - Any land area susceptible to being inundated by water from any source.

Floodproofing - any combination of structural and non-structural additions, changes, or adjustments to structures which reduce or eliminate flood damage to real estate or improved real property, water and sanitary facilities, structures and their contents.

Floodway - The channel of a river or other watercourse and the adjacent land areas that must be reserved in order to discharge the base flood without cumulatively increasing the water surface elevation more than one foot at any point within the community.

Freeboard - A factor of safety usually expressed in feet above a flood level for purposes of floodplain management. "Freeboard" tends to compensate for the many unknown factors that could contribute to flood heights greater than the height calculated for a selected size flood and floodway conditions, such as wave action, bridge openings, and the hydrological effect of urbanization in the watershed. The amount of freeboard can be established by the town as deemed appropriate for future safety.

Functionally dependent use - A use which cannot perform its intended purpose unless it is located or carried out in close proximity to water. This term includes only docking facilities, port facilities that are necessary for the loading and unloading of cargo or passengers, and shipbuilding and ship repair facilities, but does not include long-term storage or related manufacturing facilities.

Highest adjacent grade - the highest natural elevation of the ground surface prior to construction next to the proposed walls of a structure.

Historic structure - Any structure that is:

- 1) Listed individually in the National Register of Historic Places (a listing maintained by the Department of Interior) or preliminarily determined by the Secretary of the Interior as meeting the requirements for individual listing on the National Register;
- 2) Certified or preliminarily determined by the Secretary of the Interior as contributing to the historical significance of a registered historic district or a district preliminarily determined by the Secretary to qualify as a registered historic district;
- 3) Individually listed on a state inventory of historic places in states with historic preservation programs which have been approved by the Secretary of the Interior; or,
- 4) Individually listed on a local inventory of historic places in communities with historic preservation programs that have been certified either:
 - a. By an approved state program as determined by the Secretary of the Interior; or,
 - b. Directly by the Secretary of the Interior in states without approved programs.

Hydrologic and hydraulic engineering analysis - Analyses performed by a licensed professional engineer, in accordance with standard engineering practices that are accepted by the DCR and FEMA, used to determine the base flood, other frequency floods, flood elevations, floodway information and boundaries, and flood profiles.

Letters of Map Change (LOMC) - A Letter of Map Change is an official FEMA determination, by letter, that amends or revises an effective FIRM or FLS. A LOMC include:

Letter of Map Amendment (LOMA) - An amendment based on technical data showing that a property was incorrectly included in a designated special flood hazard area. A LOMA amends the current effective FIRM and establishes that a land as defined by meets and bounds or structure is not located in a special flood hazard area.

Letter of Map Revision (LOMR) - A revision based on technical data that may show changes to flood zones, flood elevations, floodplain and floodway delineations, and planimetric features. A Letter of Map Revision Based on Fill (LOMR-F), is a determination that a structure or parcel of land has been elevated by fill above the base flood elevation and is, therefore, no longer exposed to flooding associated with the base flood. In order to qualify for this determination, the fill must have been permitted and placed in accordance with the community's floodplain management regulations.

Conditional Letter of Map Revision (CLOMR) - A formal review and comment as to whether a proposed flood protection project or other project complies with the minimum NFIP requirements for such projects with respect to delineation of special flood hazard areas. A CLOMR does not revise the effective Flood Insurance Rate Map or Flood Insurance Study.

Lowest adjacent grade - the lowest natural elevation of the ground surface next to the walls of a structure.

Lowest floor - The lowest floor of the lowest enclosed area (including basement). An unfinished or flood-resistant enclosure, usable solely for parking of vehicles, building access or storage in an area other than a basement area is not considered a building's lowest floor; provided, that such enclosure is not built so as to render the structure in violation of the applicable non-elevation design requirements of Federal Code 44CFR §60.3.

Manufactured home - A structure, transportable in one or more sections, which is built on a permanent chassis and is designed for use with or without a permanent foundation when connected to the required utilities. For floodplain management purposes the term "manufactured home" also includes park trailers, travel trailers, and other similar vehicles placed on a site for greater than 180 consecutive days.

Manufactured home park or subdivision - a parcel (or contiguous parcels) of land divided into two or more manufactured home lots for rent or sale.

Mean Sea Level – for purposes of the National Flood Insurance Program, the National Geodetic Vertical Datum (NGVD) of 1929 or the North American Vertical Datum (NAVD) of 1988 to which base flood elevations shown on a community's FIRM are referenced.

New construction - For the purposes of determining insurance rates, structures for which the "start of construction" commenced on or after 9/10/1984 and includes any subsequent improvements to such structures. For floodplain management purposes, new construction means structures for which the start of construction commenced on or after the effective date of a floodplain management regulation adopted by a community and includes any subsequent improvements to such structures.

Post-FIRM structures - A structure for which construction or substantial improvement occurred on or after 9/10/1984.

Pre-FIRM structures - A structure for which construction or substantial improvement occurred after 9/10/1984.

Primary frontal dune - a continuous or nearly continuous mound or ridge of sand with relatively steep seaward and landward slopes immediately landward and adjacent to the beach and subject to erosion and overtopping from high tides and waves during major coastal storms.

Recreational vehicle - A vehicle which is:

- 1) Built on a single chassis;
- 2) 400 square feet or less when measured at the largest horizontal projection;
- 3) Designed to be self-propelled or permanently towable by a light duty truck; and,
- 4) Designed primarily not for use as a permanent dwelling but as temporary living quarters for recreational camping, travel, or seasonal use.

Repetitive Loss Structure - A building covered by a contract for flood insurance that has incurred flood-related damages on two occasions in a 10-year period, in which the cost of the repair, on the average, equalled or exceeded 25 percent of the market value of the structure at the time of each such flood event; and at the time of the second incidence of flood-related damage, the contract for flood insurance contains increased cost of compliance coverage.

Severe repetitive loss structure - a structure that:

- (1) Is covered under a contract for flood insurance made available under the NFIP; and
- (2) Has incurred flood related damage.
 - (a) For which 4 or more separate claims payments have been made under flood insurance coverage with the amount of each such claim exceeding \$5,000, and with the cumulative amount of such claims payments exceeding \$20,000; or
 - (b) For which at least 2 separate claims payments have been made under such coverage, with the cumulative amount of such claims exceeding the market value of the insured structure.

Shallow flooding area - A special flood hazard area with base flood depths from one to three feet where a clearly defined channel does not exist, where the path of flooding is unpredictable and indeterminate, and where velocity flow may be evident. Such flooding is characterized by ponding or sheet flow.

Special flood hazard area - The land in the floodplain subject to a one (1%) percent or greater chance of being flooded in any given year as determined in §28.30.

Start of construction - For other than new construction and substantial improvement, under the Coastal Barriers Resource Act (P.L. – 97-348), means the date the building permit was issued, provided the actual start of construction, repair, reconstruction, rehabilitation, addition, placement, substantial improvement or other improvement was within 180 days of the permit date. The actual start means either the first placement of permanent construction of a structure on a site, such as the pouring of slab or footings, the installation of piles, the construction of columns, or any work beyond the stage of excavation; or the placement of a manufactured home on a foundation. Permanent construction does not include land preparation, such as clearing, grading and filling; nor does it include the installation of streets and/or walkways; nor does it include excavation for a basement, footings, piers, or foundations or the erection of temporary forms; nor does it include the installation on the property of accessory buildings, such as garages or sheds not occupied as dwelling units or not part of the main structure. For a substantial improvement, the actual start of the construction means the first alteration of any wall, ceiling, floor, or other structural part of a building, whether that alteration affects the external dimensions of the building.

Structure - for floodplain management purposes, a walled and roofed building, including a gas or liquid storage tank, that is principally above ground, as well as a manufactured home.

Substantial damage - Damage of any origin sustained by a structure whereby the cost of restoring the structure to its before damaged condition would equal or exceed 50 percent of the market value of the structure before the damage occurred. It also means flood-related damages sustained by a structure on two occasions in a 10-year period, in which the cost of the repair, on the average, equals or exceeds 25 percent of the market value of the structure at the time of each such flood event.

Substantial improvement - Any reconstruction, rehabilitation, addition, or other improvement of a structure, the cost of which equals or exceeds 50 percent of the market value of the structure before the start of construction of the improvement. The term does not, however, include either:

- Any project for improvement of a structure to correct existing violations of state or local health, sanitary, or safety code specifications which have been identified by the local code enforcement official and which are the minimum necessary to assure safe living conditions, or
- 2) Any alteration of a historic structure, provided that the alteration will not preclude the structure's continued designation as a historic structure.
- 3) Historic structures undergoing repair or rehabilitation that would constitute a substantial improvement as defined above, must comply with all ordinance requirements that do not preclude the structure's continued designation as a historic structure. Documentation that a specific ordinance requirement will cause removal of the structure from the National Register of Historic Places or the State Inventory of Historic places must be obtained from the Secretary of the Interior or the State Historic Preservation Officer. Any exemption from ordinance requirements will be the minimum necessary to preserve the historic character and design of the structure.

Violation - the failure of a structure or other development to be fully compliant with the community's floodplain management regulations. A structure or other development without the elevation certificate, other certifications, or other evidence of compliance required in this ordinance is presumed to be in violation until such time as that documentation is provided.

Watercourse - A lake, river, creek, stream, wash, channel or other topographic feature on or over which waters flow at least periodically. Watercourse includes specifically designated areas in which substantial flood damage may occur.

Sections 28.70 - 28.99. Reserved.